

ST800-SA**ST800-EA**

DLAB Infrared sterilizers are designed for short time sterilization of laboratory equipments like inoculating loop, inoculated needles, tweezers and other small items with high temperature. These can also be used for the low temperatures with long time sterilization to prevent contamination.

ST800-S / ST800-E ST800-SA / ST800-EA Infrared Sterilizer

Features

- DLAB sterilizers are heating fast, convenient and can replace alcohol lamps and bunsen burners
- Sterilization is completed within 5-7 seconds
- Very safe to operate with no visual fire. It is only ashing the organic matter in the depths of ceramic heating body and preventing cross contamination
- LED display actual temperature with temp. control accuracy is 10°C
- These can be used in biology safety cabinets and clean bench space
- Precise temperature control precision and adjustable from 300 - 830°C
- Heating zone angle adjustable(ST800-SA/EA)
- Optional bracket support for inoculate loop or needle instead of holding them by hand

Specifications

	ST800-S	ST800-E	ST800-SA	ST800-EA
Display	LED	/	LED	/
Temperature range [°C]	300~830	830	300~830	830
Central zone max temperature [°C]	825±50	825±50	825±50	825±50
The heating zone adjustable angle	/	/	0-40°	0-40°
Max. outer diameter of sterilized items [mm]	15	15	15	15
The total length of heating area [mm]	140	140	140	140
Heating tube	Ceramic	Ceramic	Ceramic	Ceramic
Shell	ABS	ABS	ABS	ABS
Dimensions [LxWxH] (mm)	180x120x217	180x120x217	180x120x186	180x120x186
Weight[kg]	1.5	1.5	1.5	1.5
Voltage[V]	220V, 50/60Hz	220V, 50/60Hz	220V, 50/60Hz	220V, 50/60Hz
Power[W]	190	190	190	190
Working temperature [°C]	-10~40	-10~40	-10~40	-10~40
Working humidity [% RH]	<80	<80	<80	<80
Storage temperature [°C]	-40~60	-40~60	-40~60	-40~60
Storage humidity [% RH]	10~90	10~90	10~90	10~90